







RC91

Vitap

-  Refilatore universale
-  Universal trimming machine
-  Universal-Bündigfräsmaschine
-  Affleureuse universelle
-  Perfilador
-  Универсальный станок для снятия свесов



Dati tecnici - Technical data - Technische Daten - Données techniques Notas técnicas - Технические характеристики

Potenza motori (Kw) - Motors power - Motor Puisance de moteurs - Potencia motores - Мощность двигателя	0,7 hp 0,51 Kw
Velocità frese (r.p.m.) - Routers speed - Fräsaggregat-Drehzahl Vitesse des outils - Giros fresas - Скорость вращения фрезы	12.000
Altezza rifilatura (mm) - Trimming height - Kantenhöhe Epaisseur de afeurage - Altura refilador - Высота фрезерования	10 : 60
Spessore max. del bordo (mm) - Max tickness of the tape - Max. Kantenstärke Epaisseur des alaises - Grosor canto - Максимальная толщина кромки	3
Misure d'ingombro (mm) - Overall size - Außenmaße Mesures d'encombrement - Medidas exteriores - Габаритные размеры	780x620 x1370
Peso (Kg) - Weight - Gewicht Poids - Peso - Bec	150

RC91

OPTIONAL

- Sollevamento pneumatico del gruppo refilatore.
- Pneumatic lifting of the upper motor.
- Pneumatische Anhebung des oberen Fräsmotors.
- Système pneumatique de levage de la fraise supérieure.
- Sistema neumático suvida motores.
- Пневматический подъем верхнего двигателя.